

⑫

# EUROPEAN PATENT APPLICATION

⑰ Application number: 86101445.4

⑤① Int. Cl.<sup>4</sup>: G 07 F 7/10

G 07 G 1/12, G 07 F 7/02

⑱ Date of filing: 04.02.86

③① Priority: 04.02.85 JP 19423/85

④③ Date of publication of application:  
13.08.86 Bulletin 86/33

⑥④ Designated Contracting States:  
DE FR GB

⑦① Applicant: Kabushiki Kaisha Toshiba  
72, Horikawa-cho Saiwai-ku  
Kawasaki-shi Kanagawa-ken 210(JP)

⑦② Inventor: Kamitake, Takashi  
2-20-15 Midorigaoka Meguro-ku  
Tokyo(JP)

⑦③ Inventor: Uehara, Kiyohiko  
79 Toshiba Hiyoshi-ryo 1020 Hiyoshihonocho  
Kohoku-ku Yokohama-shi Kanagawa-ken(JP)


⑦④ Representative: Lehn, Werner, Dipl.-Ing. et al,  
Hoffmann, Eitle & Partner Patentanwälte Arabellastrasse  
4 (Sternhaus)  
D-8000 München 81(DE)

⑥⑤ Data processing system and method and pocket-size hermetically sealed electronic device.

⑥⑦ A system in accordance with the present invention is arranged to carry out data processings by selecting and combining basic functions provided in a pocket-size hermetically sealed electronic device by operating from an external equipment. The pocket-size hermetically sealed electronic device includes a mask ROM (36) which is memorizing programs for realizing a plurality of kinds of basic functions,

a RAM (38) which memorizes various kinds of data that accompany the basic functions, a connection section (40) which receives a command that includes at least function codes for selecting programs of the plurality of kinds of basic functions based on a command from the connection section, and carries out the functions in accordance with the programs selected.

FIG. 2



DATA PROCESSING SYSTEM AND METHOD AND  
POCKET-SIZE HERMETICALLY SEALED ELECTRONIC DEVICE

1 BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to a system which carries out data processing by means of a pocket-size hermetically sealed electronic device that has an electronic device sealed in its inside, and more particularly to a pocket-size hermetically sealed electronic device which can be adapted for a wide variety of services with a single unit of the device.

10

Description of the Prior Art

In recent years, development has been under way for systems such as home banking system, farm banking system, and home shopping system that can make use of the communication systems to the most advantageous degree. Along with it, development of the so-called IC card has also been advanced.

15 An IC card is a pocket-size hermetically sealed electronic device which has an electronic device with data processing capability sealed inside of the card in such a way as to make it impossible to read out those data that require privacy protection. The IC card is being utilized in the above systems for such purposes as security assurance and memory of necessary information of the data on the network, and its application to a wide variety of uses is being anticipated. Further, it is conceivable to use it in the field of financial services for storage of financial transaction information and encryption/decryption. further, its use as a key to scrambling and for storage of viewing/listening information for the pay television has been proposed by CII Honeywell Bull, Inc.

30

1 Moreover, it may be possible to be applied to the medical field  
for storage of medical information for the patients. As  
described in the above, the IC card is anticipated to be utilized  
in the future for all sorts of services that require data storage  
5 and data processing.

Now, in using IC card for various kinds of services, the  
form of the data to be stored and the type of data processing  
required are different for each service, so that service provider  
has to provide the user with an IC card which is different for  
10 different service. For this reason, it is conceivable to seal to  
the inside of the card different electronic device that is  
suitable for separate purposes, and manufacture and provide an IC  
card corresponding to each purpose of use. However, such an  
arrangement is undesirable since it leads to a rise in the cost  
15 of IC card. Then, one may wish to give a common structure to the  
hardware and cope with the variety of services by varying the  
software for the electronic device that is sealed in the inside  
of the card. In this case, it becomes necessary to provide a  
program memory in the inside of the card.

20 However, when a programmable ROM (PROM) is to be used as the  
program memory, writing of the program takes a long time such  
that for one like IC card which is to be provided to a large  
number of users there was a problem that a rise in the production  
cost was inevitable due to low mass productivity. further, for a  
25 fixed single program, it is possible to provide a card at low  
cost through mass production by using mask ROM for the program  
memory. However, in such a case it becomes impossible to provide  
a variety of softwares as mentioned in the above.

In the above mannewr, in spite of the anticipation that the  
30 existing pocket-size hermetically sealed electronic device will  
be utilized for a variety of purposes, there was a problem that  
it was difficult to provide at low cost a pocket-size  
hermiatically sealed electronic device that is applicable to a  
variety of services.

35

## 1 SUMMARY OF THE INVENTION

An object of the present invention is to provide a pocket-size hermetically sealed electronic device which enables one to receive a wide variety of services at low cost.

Another object of the present invention is to provide a pocket-size hermetically sealed electronic device which is adapted for a wide variety of services by selecting and combining via an external equipment the basic functions provided to carry out data processing.

One of the features due to the present invention is that the pocket-size hermetically sealed electronic device includes a first memory section which memorizes the program for realizing a plurality of kinds of basic functions, a second memory section which memorizes various kinds of data that accompany the basic functions, a connection section which receives a command that contains at least a function command for selecting, by means of an external equipment, the plurality of kinds of basic function programs, and a control section which selects the basic function programs by the command from the connection section and executes the basic functions in accordance with the programs selected.

These and other objects, features and advantages of the present invention will be more apparent from the following description of the preferred embodiments, taken in conjunction with the accompanying drawings.

### BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram for illustrating the function of an IC card embodying the present invention;

Fig. 2 is a block diagram which shows the concrete construction of the IC card shown in Fig. 1;

Fig. 3 is a perspective view of the IC card shown in Figs. 1 and 2;

Fig. 4 is a perspective view of a data processing system which uses the IC card shown in Figs. 1 to 3;

1        Fig.5 is a compositional block diagram for the system shown  
in Fig.4;

      Fig.6 is a compositional block diagram for the card  
reader/writer in Fig.5;

5        Fig.7 is a flow chart for illustrating the operation of the  
terminal of the system shown in Fig.4;

      Fig.8 is a flow chart for illustrating the operation of the  
card reader/writer of the system shown in Fig.4;

      Fig.9 illustrates simplified diagrams that show the data  
10 format for the data to be sent from the card reader/writer to the  
IC card shown in Fig.4;

      Fig.10 is a flow chart for illustrating the operation of the  
IC card of the system shown in Fig.4;

      Fig.11 is a flow chart for illustrating the sequence when  
15 the system shown in Fig.4 is applied to the credit card system;  
and

      Fig.12 is a flow chart for illustrating the sequence when  
the system shown in Fig.4 is applied to the transfer system  
through bank.

20

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Figs.4 and 5, there is shown an IC card system  
10 embodying the present invention in which the system 10 is  
25 constructed so as to have an IC card 12 connectable to a terminal  
16 via a card reader/writer 14, and a keyboard 18, a CRT display  
20, a printer 22, and a floppy disk 24 connected to the terminal  
16.

The IC card 12 which is kept by the user is for carrying out  
30 such operations as the referencing of the key data that is known  
to the user alone and the storing of necessary data in, for  
instance, purchasing a merchandise. As the diagram for its  
functions shown in Fig.1 indicates, the card 12 is composed of  
the parts for executing basic functions, such as an R/W section  
35 26, an encryption/decryption section 28, and a password

1 setting/password collation section 30, and a supervisor 32 which  
supervises these basic functions. The R/W section 26 has a  
function for reading the data from the data memory in the IC card  
12 or for writing a data in the data memory. The  
5 encryption/decryption section 28 is for carrying out the  
encryption for the data to be communicated in order to prevent  
leakage or falsification in such a case as transmitting a data  
from the terminal 16 to another terminal, or for carrying out the  
decryption of the encrypted data. The data processing there, is  
10 carried out in accordance with an encryption algorithm which has  
a sufficiently high encryption capability such as the data  
encryption standard (DES). The password setting/password  
collation section 30 is the section for memorizing the passnumber  
(key data) set up by the user, and gives a permission for the  
15 subsequent processing by carrying out the collation of the key  
data that is input after setting of the password. Further, the  
supervisor 32 interprets the function code or the function code  
supplemented by a code that is sent from the card reader/writer,  
and causes the selection and execution of the required functions  
20 from among the basic functions.

In order to accomplish these functions, the IC card is  
composed of, as shown by Fig.2, a CPU 34, a program memory 36, a  
data memory 38, an I/O interface 40, and a contact section 42.  
The program memory 36 which consists of a mask ROM is for  
25 memorizing the programs of the CPU 34 that are equipped with  
subroutines in order to realize the various basic functions. The  
data memory 38 comprises a PROM and is divided into a plurality  
of zones  $A_1, A_2, \dots, A_n$  with various kinds of access conditions  
assigned to separate zones, such as a zone from which read alone  
30 of the data is possible using an external equipment, a zone for  
which write alone is possible, a zone for which both of read and  
write are possible, a zone for which both of read and write are  
not possible, and a zone for which read and write are possible  
only after collating of the password is completed. These  
35 circuits are integrated in the form of an LSI 41 which is sealed

1 hermetically in the card 12. It is arranged to be connectable to  
an external equipment only through the contact section 42. The  
contact section 42 has a total of eight terminals 46 such as  
those for power source, for inputting clock signals, for reset,  
5 and for inputting and outputting of data.

The card reader/writer 14 transfer function code data  
between the IC card 12 and the terminal 16. It possesses a  
function to decompose a macro instruction received from the  
terminal 16 into commands for IC card, and supplies the commands  
10 to the IC card 12 in succession. More specifically, the card  
reader/writer 14 includes, as shown by Figs. 5 and 6, a  
transportation mechanism 48 which transports the IC card 12 that  
is inserted to the card insertion port 14a to a prescribed  
position, an IC card contact section 50 which makes an electrical  
15 contact with the contact section 42 of the IC card 12 that is set  
at the prescribed position, a control circuit 52 which controls  
the device as a whole, and an I/O interface 54 which transfers  
function code or data between the terminal 16.

The terminal 16 is composed of a CPU 16a and a memory 16b as  
20 shown in Fig. 5, and in response to the user's demand which is  
input via the keyboard 18 determines selection and combination of  
function codes to be given to the card reader/writer 14 by  
reading the required data processing programs that are memorized  
in the memory 16b or the floppy disk unit 24. The user receives  
25 the message from the terminal 16 via the CRT display 20 or the  
printer 22.

Next, the operation of the system in accordance with the  
embodiment constructed as in the above will be described.

As shown by Fig. 7, in a stationary state as represented by  
30 step 100 the terminal 16 is in the state which is waiting for a  
command from the user. As a command from the user is input, the  
terminal 16 analyzes the command (step 102) and determines the  
selection of necessary functions and their sequence (step 104).  
When the sequence is determined the terminal 16 outputs necessary  
35 command (function code) to the card reader/writer 14 (step 106).

- 1 Then, the terminal 16 will remain in the state of waiting until it receives from the card reader/writer 14 a response that indicates the completion of the processing required by the command (step 108). Upon receipt of a response, it judges
- 5 whether it is a final response. If it is not a final response, it sends out again a command to the card reader/writer 14 in accordance with the sequence, and if it is a final response, it returns to the state of waiting for a command from the user (step 110).
- 10 In step 120, when the card reader/writer 14 is in a stationary state, it is in the state of waiting for a command from the terminal as shown by Fig. 8. When a command is input, it judges whether the IC card is in execution (step 122), and if it is found to be executing, it goes back again to the state of
- 15 waiting for a command after outputting a response which indicates that it is a multiple command error to the terminal 16 (step 124). If the IC card is found to be not in execution, it judges the command from the terminal 16 to determine a set of command sequence to be given to the IC card 12 (step 126). Following
- 20 that, it outputs the first command to the IC card 12 (step 128). Then, it goes to the state of waiting for a response from the IC card 12 (step 130). When a response from the IC card 12 is received, it judges whether there still remains some commands to be given to the IC card (step 132), and if it is found that there
- 25 are some, it returns to step 128 to repeat outputting of the command. Otherwise, it outputs a response to the terminal 16 (step 134).

The command to be output from the card reader/writer 14 to the IC card 12 has the format with prescribed bit length as

30 indicated in Fig. 9, with a form which contains a function code alone as shown by Fig. 9a or a form which contains a function code augmented by a data as shown by Fig. 9b.

In its stationary state, the IC card 12 is in the state of waiting for a command from the card reader/writer 14 as shown by

35 Fig. 10 (step 140). When a command is input, it executes the



1 basic functions in accordance with the command (142) and outputs  
the response to the card reader/writer 14 (step 144). Then, it  
goes back to its original state of waiting.

The response in this case is supplemented by the command  
5 that was input originally, to provide for a protective measure  
for the case where the sequence between the card reader/writer 14  
is disturbed.

It should be noted as shown in the above embodiment that it  
is convenient to render the command system to be successively  
10 more macro as one goes upstream along IC card 12 → card  
reader/writer 14 → terminal 16. With such an arrangement the  
preparation of application programs in the upstream will become  
very easy.

Next, a concrete examples of operation of the system will be  
15 described.

Figure 11 shows an example of credit card system. It is  
assumed here that the sequence for the credit card system for the  
terminal 16 has already been determined. The user first inserts  
his IC card 12 into the card reader/writer 14. The card  
20 reader/writer 14 outputs a signal that informs that an IC card 12  
is inserted, to the terminal 16. Based on this, the terminal 16  
urges the user to input his passnumber. When the user inputs the  
passnumber the terminal 16 outputs the passnumber and the  
password collation instruction to the card reader/writer 14. The  
25 card reader/writer 14 outputs the passnumber and the password  
collation instruction to the IC card 12. The IC card 12 executes  
the password setting/password collation function to compare and  
refer the input passnumber with the passnumber memorized in its  
inside. When the result of the collation is affirmative, the IC  
30 card 12 outputs the response to the card reader/writer 14. The  
card reader/writer gives a permission to input, to the terminal  
16. Based on this, the terminal urges the user to input the sum  
of purchase of merchandises. When the user inputs the sum of the  
purchase, the terminal 16 requests a list of past purchases from  
35 the card reader/writer 14. This request command is given in

1 the form of a macro instruction, and the card reader/writer 14  
outputs a read command to the IC card based on it. In response  
to this command the IC card 12 executes the R/W function to  
outputs the data on the previous purchases that is memorized in  
5 its inside. The read command will remain in effect until the  
final response is received from the IC card 12, and the purchase  
list read during that time is held in the card reader/writer 14.  
In this case, in order to avoid inputting of a plurality of  
commands in the inside of the IC card 12, care is to be taken  
10 that a next command is output after a response is returned. When  
the final response from the IC card 12 is received, the card  
reader/writer 14 outputs the entirety of the purchase list to the  
terminal 16. The terminal 16 computes the balance to be  
applicable to the purchase for the IC card from the list, and  
15 outputs a write command for purchase sum to the card  
reader/writer 14 only when the purchase sum is less than the  
balance. This command, too, is given as a macro instruction, and  
the card reader/writer 14 outputs repeatedly the write command of  
data, to the IC card 12. The reason for repeating the writing of  
20 data is that a single write is not sufficient to write the  
entirety of the data. The IC card 12 executes the R/W function  
in accordance with the command, and makes entry of the new  
purchase sum in the purchase list of merchandises. When the card  
reader/writer 14 received the final response, the completion of  
25 inputting is informed to the terminal 16. The terminal 16  
displays the balance on the CRT display 20, and outputs a message  
that indicates the end of the processing, completing the purchase  
of a merchandise by means of the credit card system.

Next, an example of application of the IC card to the  
30 transfer system through bank will be described by referring to  
Fig. 12.

It will be assumed that the terminal 16 has already  
determined the sequence for the transfer system through bank.  
Form insertion of the credit card 12, through password collation,  
35 and up to input permission by the card reader/writer 14 are

1 carried out based on the procedure similar to the credit card  
system described in the above. Then, the terminal 16 urges the  
user to input necessary transfer data such as the bank account  
number of the payee, the bank account number of the payer, and  
5 the sum of transfer. When the user inputs the transfer data, the  
terminal 16 outputs an instruction for encrypting the transfer  
data to the card reader/writer 14. This instruction is given in  
the form of a macro instruction, and based on this, the card  
reader/writer 14 outputs to the IC card 12 an encrypted command  
10 supplemented by the transfer data. The IC card 12 executes the  
encryption/decryption function, and outputs an encrypted data to  
the card reader/writer 14. The card reader/writer 14 stores the  
encrypted data in its inside until completion of the encryption  
of the transfer data. After the encryption of the transfer data,  
15 the card reader/writer 14 outputs the encrypted data to the  
terminal 16 upon receipt of the final encrypted data. The  
terminal 16 transmits the encrypted data to the terminal for the  
other party (bank) via a circuit. In response to this, the  
terminal of the other party transmits a signal which acknowledges  
20 the receipt of the data, where the signal transmitted is an  
encrypted data too. When this data is received the terminal 16  
outputs a decryption instruction along with the received data to  
the card reader/writer 14. This instruction is also a macro  
instruction so that the card reader/writer 14 outputs  
25 continuously the decryption instruction, to the IC card 12.  
Based on the instruction the IC card 12 executes the  
encryption/decryption function in its inside, and outputs the  
decrypted data obtained to the card reader/writer 14. Upon  
receipt of the final decrypted data, the card reader/writer 14  
30 outputs the entirety of the decrypted data to the terminal 16.  
Then, in order to keep a documentary evidence in the inside of  
the IC card 12, the terminal 16 outputs the transfer data and the  
received data along with a write command, to the card  
reader/writer 14. The command is also a macro command, and the  
35 card reader/writer 14 outputs continuously the write command to  
the IC card 12. The IC card 12 executes the R/W function in its

1 inside and stores the above data in its inside. Upon receipt of  
the final response from the IC card 12, the card reader/writer 14  
outputs a signal that indicates the completion of inputting to  
the terminal 16. The terminal 16 outputs the message that  
5 indicates the completion of transfer on the CRT display 20. With  
this, the transfer operation by means of the transfer system  
through bank is completed.

In this manner, according to the present embodiment the  
software that determines the function selection and the  
10 processing sequence in the inside of the IC card 12, through the  
operation on the terminal 16, can be constructed at will by the  
provider of the service so that it is possible to meet a wide  
variety of data processing requirements. This becomes possible  
due to the circumstance that a plurality of basic functions are  
15 given to the IC card 12 and that an arrangement is made to permit  
a selective execution of these basic functions. These basic  
functions are not limited to those described in the foregoing so  
that the utility of the present invention can be increased  
greatly by arranging the functions to be applicable to all sorts  
20 of services and be of general use and basic character.

It is to be noted that although the IC card is described in  
conjunction with the pocket-size hermetically sealed electronic  
device, the present invention is not limited to a card-like  
structure and may be applied to structures of block-like or  
25 pencil-like. Moreover, the hardware construction of the  
electronic device will also permit various modifications within  
the scope which does not deviate from the main contents of the  
invention.

30

35

1 CLAIMS

1. A system which carries out data processing, comprising:

5 (a) a pocket-size hermetically sealed electronic device, comprising;

a first memory section which has memorized programs for accomplishing a plurality kinds of basic functions,

10 a second memory section for memorizing various kinds of data used for the basic functions,

a connection section for supplying a command which includes at least function codes for selecting programs of the plurality kinds of basic functions, and

15 a control section for selecting the programs of basic functions by the command from the connection section to execute the basic functions in accordance with the program selected; and

(b) an external equipment for supplying to the connection section the command with function codes that select the programs  
20 of the plurality kinds of basic functions through contact with the connection section, and for receiving from the connection section a response signal for the basic function executed.

2. A system as claimed in claim 1, wherein the plurality of  
25 kinds of the basic functions include a read/writer function of the data from the second memory section, a encryption/ decryption function for preventing leakage and falsification of the communication data, and a password setting/password collation function.

30

3. A system as claimed in Claim 1, wherein the pocket-size hermetically sealed electronic device comprises an IC card formed in the card-like structure.

35 4. A system as claimed in Claim 1, wherein the first memory section comprises a mask ROM.

- 1 5. A system as claimed in Claim 1, wherein the second memory  
section comprises a PROM, and in which the control section  
comprises a CPU.
- 5 6. A system as claimed in Claim 3, wherein said external  
equipment comprises a keyboard, a memory unit, an IC card  
reader/writer, and a CPU which reads the data processing programs  
memorized in the memory unit, in response to the command which is  
inputted via the keyboard, to select and combine the function  
10 codes to supply the result to the IC card reader/writer, and also  
executes prescribed processings by receiving a response signal of  
the IC card from the IC card reader/writer.
- 15 7. A system as claimed in Claim 6, wherein the IC card reader/  
writer comprises a transportation mechanism for transporting the  
IC card inserted to a insertion port to a prescribed position, an  
IC card contact section which is to be brought to an electrical  
connection with the connection section of the IC card that is set  
at the prescribed position, an I/O interface for carrying out  
20 transfer of command from/to the CPU of said external equipment,  
and a control circuit for controlling the transportation  
mechanism, and the I/O interface.
- 25 8. A system as claimed in Claim 1, wherein the command  
supplied by said external equipment comprises a function code and  
a data.
- 30 9. A system as claimed in Claim 1, wherein said second memory  
section of the pocket-size hermetically sealed electronic device  
is divided into a plurality of zones assigned separately with  
different access conditions.
- 35 10. A system as claimed in Claim 2, wherein said second memory  
section of the pocket-size hermetically sealed electronic device  
is divided into a zone from which read alone is

1 possible, a zone for which write alone is possible, a zone for  
which both of read and write are possible, a zone for which both  
of read and write are not possible, and a zone for which read and  
writer are possible only after completion of the password  
5 collation, with respect to the external equipment.

11. In a system which carries out data processing by means of a  
pocket-size hermetically sealed electronic device in which an  
electronic device with data processing function is sealed a data  
10 processing method, comprising the steps of:

(a) storing programs for accomplishing a plurality of kinds  
of basic functions in the pocket-size hermetically sealed  
electronic device;

(b) supplying a command, which includes at least function  
15 codes that select programs the plurality of kinds of basic  
functions, to the pocket-size hermetically sealed electronic  
device;

(c) selecting programs for basic functions based on the  
command from the connecting section; and executing the basic  
20 functions in accordance with the programs selected.

12. A data processing method as claimed in Claim 11, wherein  
the plurality kinds of basic functions includes a read/writer  
function of data from the secon memory section, an  
25 encryption/decryption function for preventing leakage and  
falsification of communication data, and password setting/  
password collation function.

13. In a system which carries out data processing a pocket-size  
30 hermetically sealed electronic device, comprising:

(a) a first memory section which has memorized programs for  
accomplishing a plurality kinds of basic functions;

(b) a second memory section for memorizing various kinds of  
data used for the basic functions;

35

1 (c) a connection section for receiving a command, which  
includes at least function codes for selecting programs of the  
plurality kinds of basic functions, from an external equipment in  
the system; and

5 (d) a control section for selecting the programs for basic  
functions by a command from the connection section to accomplish  
the basic functions in accordance with the programs selected.

14. A pocket-size hermetically sealed electronic device as  
10 claimed in Claim 13, wherein the plurality kinds of basic  
functions include a read/write function of data from the second  
memory section, an encryption/decryption function for preventing  
leakage and falsification of communication data, and a password  
setting/password collation function.

15

15. A pocket-size hermetically sealed electronic device as  
claimed in Claim 13, wherein said pocket-size hermetically  
sealed electronic device comprises an IC card.

20 16. A pocket-size hermetically sealed electronic device as  
claimed in Claim 13, wherein the first memory section comprises  
a mask ROM.

17. A pocket-size hermetically sealed electronic device as  
25 claimed in Claim 13, wherein the second memory section comprises  
a PROM and said control section comprises a CPU.

18. A pocket-size hermetically sealed electronic device as  
claimed in Claim 13, wherein the external equipment comprises a  
30 keyboard, a memory unit, an IC card reader/writer, and a CPU  
which reads the data processing programs memorized in the memory  
unit in response to the command which is sent via the keyboard,  
to select and combine the function codes to supply the result to  
the IC card reader/writer, and also executes prescribed  
35 processings by receiving a response signal of the IC card from  
the IC card reader/writer.



- 1 19.. A pocket-size hermetically sealed electronic device as  
claimed in Claim 18, wherein the IC card reader/writer comprises  
a transportation mechanism for transporting the IC card inserted  
to a insertion port to a prescribed position, an IC card contact  
5 section which is to be electrical-connected with the connection  
section of the IC card that is set at the prescribed position, an  
I/O interface for carrying out transfer of command from/to the  
CPU of said external equipment, and a control circuit for  
controlling the transportation mechanism and the I/O interface.  
10
20. A pocket-size hermetically sealed electronic device as  
claimed in Claim 13, wherein the command supplied by the  
external equipment comprises a function code and a data.
- 15 21. A pocket-size hermetically sealed electronic device as  
claimed in Claim 13, wherein said second memory section is  
divided into a plurality of zones assigned separately with  
different access conditions.
- 20 22. A pocket-size hermetically sealed electronic device as  
claimed in Claim 14, wherein said second memory section is  
divided into a zone from which read alone is possible, a zone for  
which write alone is possible, a zone for which both of read and  
write are possible, a zone for which both of read and write are  
25 not possible, and a zone for which read and write are possible  
only after completion of the password collation, with respect to  
the external equipment.

30

35

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9a




FIG. 9b




FIG. 10






FIG. 11





8/8

FIG.12



***This Page Blank (uspto)***

12

# EUROPEAN PATENT APPLICATION

21 Application number: 86101445.4

51 Int. Cl.<sup>3</sup>: G 07 F 7/10  
G 07 G 1/12, G 07 F 7/02

22 Date of filing: 04.02.86

30 Priority: 04.02.85 JP 19423/85

43 Date of publication of application:  
13.08.86 Bulletin 86/33

68 Date of deferred publication of search report: 21.09.88

84 Designated Contracting States:  
DE FR GB

71 Applicant: KABUSHIKI KAISHA TOSHIBA  
72, Horikawa-cho Saiwai-ku  
Kawasaki-shi Kanagawa-ken 210(JP)

72 Inventor: Kamitake, Takashi  
2-20-15 Midorigaoka Meguro-ku  
Tokyo(JP)

72 Inventor: Uehara, Kiyohiko  
79 Toshiba Hiyoshi-ryo 1020 Hiyoshihoncho  
Kohoku-ku Yokohami-shi Kanagawa-ken(JP)

74 Representative: Lehn, Werner, Dipl.-Ing. et al,  
Hoffmann, Eitle & Partner Patentanwälte Arabellastrasse  
4  
D-8000 München 81(DE)

54 Data processing system and method and pocket-size hermetically sealed electronic device.

57 A system in accordance with the present invention is arranged to carry out data processings by selecting and combining basic functions provided in a pocket-size hermetically sealed electronic device by operating from an external equipment. The pocket-size hermetically sealed electronic device includes a mask ROM (36) which is memorizing programs for realizing a plurality of kinds of basic functions, a RAM (38) which memorizes various kinds of data that accompany the

basic functions, a connection section (40) which receives a command that includes at least function codes for selecting programs of the plurality of kinds of basic functions, and a CPU (34) which selects programs for the basic functions based on a command from the connection section, and carries out the functions in accordance with the programs selected.




FIG. 2



European Patent  
Office

# EUROPEAN SEARCH REPORT

0190733

Application Number

EP 86 10 1445

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
Y	DE-A-2 738 113 (DETHLOFF) * Page 11, lines 8-18; page 12, lines 7-21; page 14, lines 1-19, line 26 - page 15, line 14; page 18, line 13 - page 20, line 16; page 21, line 24 - page 22, line 12; figures 1,2,7,8 *	1-3,5,6 9-15, 17,18, 21,22	G 07 F 7/10 G 07 G 1/12 G 07 F 7/02
Y	IEEE SPECTRUM, vol. 21, no. 2, February 1984, pages 43-49, IEEE, New York, US; S.B. WEINSTEIN: "Smart credit cards: the answer to cashless shopping" * Whole document *	1-3,5,6 9-15, 17,18, 21,22	
A	GB-A-2 140 179 (AMERICAN EXPRESS CO.) * Page 4, line 127 - page 5, line 26; page 6, lines 55-123; page 7, lines 76-82, line 108 - page 8, line 22; figures 1,2,5,7 *	1-3,5,6 9,11- 15,17, 18,21	
A	EP-A-0 057 602 (D.A. CHALMERS) * Page 2, line 1 - page 3, line 35; figure 2 *	1,6,9, 11,13, 18,21	
A	FR-A-2 477 303 (ELECTRONIQUE MARCEL DASSAULT) * Page 1, lines 18-23; page 3, line 34 - page 5, line 9, line 39 - page 6, line 1; figures 1-6,8 *	3,7,15, 19	G 07 F G 07 G G 06 K
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 11-07-1988	Examiner RAHNER
CATEGORY OF CITED DOCUMENTS			
X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document		T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P0401)